

Alto L

The compact alternative - with respect to size, weight and price/performance ratio.

Product description

- The compact alternative - with respect to size, weight and price/performance ratio.
- Very lightweight but extremely stable.
- Rung depth 30 mm.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.

Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load capacity: max. 150 kg
 Material: aluminium
 Standards: EN 131 professional
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 270 mm
 Warranty: 10 years



to the product



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41547	7	2.21 m	58 mm	2.210 mm × 350 mm × 60 mm	4 kg		3.05 m
41548	8	2.49 m	58 mm	2.490 mm × 350 mm × 60 mm	4.4 kg		3.35 m
41550	10	3.05 m	58 mm	3.050 mm × 350 mm × 60 mm	6.1 kg	0.79 m	3.9 m
41552	12	3.61 m	58 mm	3.610 mm × 350 mm × 60 mm	7 kg	0.79 m	4.4 m
41554	14	4.17 m	68 mm	4.170 mm × 350 mm × 65 mm	8 kg	0.79 m	4.95 m
41556	16	4.73 m	68 mm	4.730 mm × 350 mm × 70 mm	9.2 kg	0.89 m	5.5 m
41558	18	5.29 m	73 mm	5.290 mm × 350 mm × 80 mm	10.5 kg	0.89 m	6.05 m
41560	20	5.85 m	73 mm	5.850 mm × 350 mm × 80 mm	11.5 kg	0.99 m	6.6 m
41562	22	6.41 m	85 mm	6.410 mm × 350 mm × 80 mm	13.2 kg	0.99 m	7.15 m
41564	24	6.98 m	85 mm	6.970 mm × 350 mm × 90 mm	14.4 kg	1.1 m	7.7 m
