

Everest 2E

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From a ladder length of 8.30 m, the upper ladder is equipped with abrasion resistant wall wheels.
- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- High level of stability thanks to extra-wide lower ladder (490 mm).
- Plastic anti-friction insert with lift-off retainer.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



to the product



Product features

Castors: Rubber
 Coating: natural
 Connection between stiles and rungs/stiles: flanged
 External width of lower ladder: 490 mm
 Load capacity: max. 150 kg
 Material: aluminium
 Standards: EN 131 professional
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 270 mm
 Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight
40245	6	2 × 6	2.95 m	1.83 m	58 mm	1.830 mm × 500 mm × 130 mm	6 kg
40246	8	2 × 8	4.07 m	2.39 m	68 mm	2.390 mm × 500 mm × 130 mm	9.8 kg
40247	10	2 × 10	4.96 m	3 m	68 mm	3.000 mm × 500 mm × 140 mm	13.5 kg
40248	12	2 × 12	6.09 m	3.56 m	73 mm	3.570 mm × 500 mm × 160 mm	18 kg
40249	14	2 × 14	7.21 m	4.07 m	85 mm	4.130 mm × 500 mm × 160 mm	19.5 kg
40214	16	2 × 16	8.33 m	4.7 m	98 mm	4.690 mm × 500 mm × 180 mm	25 kg
40215	18	2 × 18	9.13 m	5.2 m	98 mm	5.210 mm × 500 mm × 230 mm	27.5 kg
40216	20	2 × 20	10.25 m	5.74 m	114 mm	5.770 mm × 500 mm × 230 mm	33 kg
40217	24	2 × 24	12.22 m	6.9 m	114 mm	6.900 mm × 500 mm × 230 mm	41.54 kg



Order number	Wide crosspiece	Working height
40245		3.8 m
40246	0.9 m	4.85 m
40247	1 m	5.75 m
40248	1.1 m	6.8 m
40249	1.2 m	7.9 m
40214	1.2 m	9 m
40215	1.2 m	9.75 m
40216	1.2 m	10.85 m
40217	1.2 m	12.75 m