



Variomax V

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

Product description

- Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.
- Single ladder, stepladder and stair ladder in one.
- Easy-to-use, automatically engaging aluminium safety hinge.
- Safe height adjustment thanks to four pull handles of diecast aluminium.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance EN131-1 (except for the 4x3 model).
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Rung by rung height adjustment in increments of 280 mm.
- Quickly and easily converts from one mode to another.
- High strength, non-twist rung/stile connections.



Product features

Coating	Connection between stiles and rungs/stiles	Dimensions, folded	Load capacity	Material
---------	--	--------------------	---------------	----------



natural	flanged	Missing translation	max. 150 kg	aluminium
Standards EN 131-4	Tread depth 30 mm	Type of rungs/treads serrated	Vertical distance between each rung/tread 265 mm	Warranty 10 years

Product variants

SKU 41934	SKU 41383	SKU 41384
Length as lean-to ladder 2.97 m	Length as lean-to ladder 4.2 m	Length as lean-to ladder 5.3 m
Length as trestle 1.45 m	Length as trestle 2 m	Length as trestle 2.54 m
Number of rungs 4 × 3	Number of rungs 4 × 4	Number of rungs 4 × 5
Transport dimensions 970 mm × 500 mm × 210 mm	Transport dimensions 1.310 mm × approx. 640 mm × 210 mm	Transport dimensions 1.580 mm × approx. 710 mm × 210 mm
Weight 9 kg	Weight 15 kg	Weight 18 kg
Working height as lean-to ladder 3.85 m	Working height as lean-to ladder 5 m	Working height as lean-to ladder 6.05 m
Working height as stepladder 2.75 m	Working height as stepladder 3.35 m	Working height as stepladder 3.85 m
SKU		



41385

Length as lean-to ladder

6.4 m

Length as trestle

3.1 m

Number of rungs

4 × 6

Transport dimensions

1.860 mm × approx. 780 mm × 210 mm

Weight

22 kg

Working height as lean-to ladder

7.1 m

Working height as stepladder

4.4 m